

## LR32-02-00



**Product Categories:** [LR Series Pilot Relief Valves](#)

**Product Tags:** [AXIAL PISTON PUMPS](#), [CARTRIDGE VALVE](#), [CHECK VALVE](#), [CONTROL VALVE](#), [CYLINDER](#), [Directional valve](#), [ELECTRIC ACTUATORS](#), [FLOW CONTROL](#), [Flow control valve](#), [GAUGE](#), [GEAR PUMPS](#), [HAND LEVER VALVE](#), [HLSV SOLENOID DIRECTIONAL VALVES](#), [HOUSING FOR PUMPS](#), [Hydraulic](#), [HYDRAULIC CYLINDERS](#), [HYDRAULIC FILTERS](#), [HYDRAULIC MOTORS](#), [HYDRAULIC POWER PACK](#), [HYDRAULIC UNITS](#), [Hydraulics](#), [HYDRAULICS HAND PUMPS](#), [Lift valve](#), [LR PILOT RELIEF VALVE](#), [LT/LTC FLOW CONTROL VALVE](#), [LVC CHEK VALVE](#), [Modular valve](#), [MOTORS](#), [PISTON PUMPS](#), [Pneumatic](#), [PNEUMATIC ACTUATOR](#), [PNEUMATIC ANGLE VALVES](#), [PNEUMATIC CYLINDERS](#), [Pneumatics](#), [Pressure switch](#), [Pressure valve](#), [PROPORTIONAL DIRECTIONAL CONTROL VALVES](#), [PROPORTIONAL HYDRAULICS](#), [Proportional valve](#), [PUMP](#), [PUMP HYDRAULICS](#), [RADIAL PISTON PUMPS](#), [RELIEF VALVES](#), [SF SHUTTELE VALVE](#), [SOLENOID DIRECTIONAL VALVES](#), [SOLENOID VALVE](#), [TORK](#), [TORK hydraulic](#), [TORK hydraulics](#), [TORK Pneumatic](#), [TORK pneumatics](#), [TURK](#), [VALVE](#), [VANE PUMPS](#), [YF DIRECT RELIEF VALVE](#)

**Product Page:** <http://torkhydraulics.com/product/lr32-02-00/>

## Technical specification

Max. working pressure: 315bar

Max. flow rate: See pressure drop-flow curve

Pressure range: 1~250bar

Internal leakage:  $\leq 30$ ml/min

Operating temperature: -30~+110°C

Oil clearness: 25u m or better

Standard setting pressure: 160bar