

THF3 Series Power Packs for lift



Product Categories: [Compact Hydraulic Power Pack Series](#)

Product Tags: [AXIAL PISTON PUMPS](#), [CARTRIDGE VALVE](#), [CHECK VALVE](#), [CONTROL VALVE](#), [CYLINDER](#), [Directional valve](#), [ELECTRIC ACTUATORS](#), [FLOW CONTROL](#), [Flow control valve](#), [GAUGE](#), [GEAR PUMPS](#), [HAND LEVER VALVE](#), [HLSV SOLENOID DIRECTIONAL VALVES](#), [HOUSING FOR PUMPS](#), [Hydraulic](#), [HYDRAULIC CYLINDERS](#), [HYDRAULIC FILTERS](#), [HYDRAULIC MOTORS](#), [HYDRAULIC POWER PACK](#), [HYDRAULIC UNITS](#), [Hydraulics](#), [HYDRAULICS HAND PUMPS](#), [Lift valve](#), [LR PILOT RELIEF VALVE](#), [LT/LTC FLOW CONTROL VALVE](#), [LVC CHEK VALVE](#), [Modular valve](#), [MOTORS](#), [PISTON PUMPS](#), [Pneumatic](#), [PNEUMATIC ACTUATOR](#), [PNEUMATIC ANGLE VALVES](#), [PNEUMATIC CYLINDERS](#), [Pneumatics](#), [Pressure switch](#), [Pressure valve](#), [PROPORTIONAL DIRECTIONAL CONTROL VALVES](#), [PROPORTIONAL HYDRAULICS](#), [Proportional valve](#), [PUMP](#), [PUMP HYDRAULICS](#), [RADIAL PISTON PUMPS](#), [RELIEF VALVES](#), [SF SHUTTELE VALVE](#), [SOLENOID DIRECTIONAL VALVES](#), [SOLENOID VALVE](#), [TORK](#), [TORK hydraulic](#), [TORK hydraulics](#), [TORK Pneumatic](#), [TORK pneumatics](#), [TURK](#), [VALVE](#), [VANE PUMPS](#), [YF DIRECT RELIEF VALVE](#)

Product Page: <http://torkhydraulics.com/product/thf3-series-power-packs-for-lift/>

Technical specification

DC Motor	Speed (r/m)	2800
	Rotation	CW
	Duty	S3
	Ingress protection	IP54
Hydraulic fluid		Mineral oil
Seal material		NBR seals
Temperature range (°C)		-30 to +80
Viscosity range (mm²/s)		2.8 to 500
Oil cleanliness class according to ISO4406		Class 20/18/15

Notes

1. The power unit can work continuously
2. Clean all hydraulic parts before mounting the power pack.
3. First oil changing is after initial 100 hours running time. After that, do oil changing every 3000 hours.

Ordering Details

How to order

THF3	- D2 / 1.6		- G2.0	- SRH4			
Product type	Electric motor		Gear pump	Oil tank			
Application	Voltage	Power	Displacement	Material	Section	Mounting	Capacity
Power packs for lift	D1: DC12 D2: DC24	1.6: 1.6KW 2.0: 2.0KW 2.5: 2.5KW	G1.6: 1.6cc/r G2.0: 2.0cc/r G2.5: 2.5cc/r G4.0: 4.0cc/r	S: Steel	R: Round	H: Horizontal V: Vertical	4: 4L 5: 5L 6: 6L 8: 8L

- P21	G24	M	- 4G
Relief valve	Solenoid valve		Oil port
System pressure	Voltage	Manual override	Thread type & size
P10: 10MPa P16: 16MPa P21: 21MPa	G12: DC12 G24: DC24	No code: Standard M: Manual override	4G: BSP 1/4" 6G: BSP 3/8" 4S: SAE 4 6S: SAE 6

Remark

Please contact us for special requirements such as different motor power & speed, pump displacement, tank material & capacity or oil port type.

Product Gallery



